
外球面轴承,轴承座单元


三螺栓和四螺栓 d 40-60mm-RAY401)

参数信息:







 GRA



RA, RAY



GRA



RA

| 单元: | RAY401) |
|---------|--------------------|
| 轴承座: | FLAN80- MSB(2件) |
| 外球面球轴承: | GAY40-N PP-B |
| 质量 kg: | 1.25 |

| _ | _ | $\overline{}$ | _ | |
|------|---|---------------|---|---|
| - 1- | ⇁ | _ | г | • |
| , | ` | ٠. | | ٠ |

型号:


| d: | 40 |
|----------------|-------|
| Н: | 147.5 |
| S: | 3.5 |
| N: | 13.5 |
| В: | 39.5 |
| B: | - |
| J: | 119 |
| d max. : | - |
| A: | 10.3 |
| U: | 32.5 |
| V: | 90 |
| 螺栓安装孔数量 n: | 4 |
| 轴承座的承载能力 N: | 7700 |
| | |

基本额定载荷:

| 动载荷 N: | 32500 |
|--------|-------|
| 静载荷 N: | 19800 |

LDG 三螺栓和四螺栓 d 40-60mm【RAY401)|】--PDF 四川科顿工贸有限公司 sckdgm.com

TEL:028-86647289



RAY